



SERIES 8050

VINYL SIDE-LOAD SINGLE HUNG WINDOW


- + **Removable bottom sash**
- + **Industry leading .01 cfm/ft. air infiltration performance**
- + **Multi-cavity vinyl lineals** improve thermal performance and enhance sound absorbency
- + **Insulating glass** provides energy saving thermal efficiency
- + **Fusion welded frame and sash** minimizes air and water infiltration and enhances overall durability
- + **Sweep lock** helps provide a weather-tight seal and added security
- + **Removable operable sash** includes full-length interlock and bottom weather reflector
- + **Dual screw boss**, metal reinforced meeting rail provides added strength
- + **Custom sized** to the nearest 1/8"
- + **Dual weather-stripping** helps block air and water infiltration, keeping harsh elements outside and energy saving comfort inside
- + **Versatile half-screen*** installed from the inside or outside
- + **Sloped sill** reduces air infiltration and accommodates easy water run-off
- + **Built-in accessory channels** accommodate multiple installation options
- + **Transferable, limited lifetime warranty**
- + **DP Rating R50** (window size tested 36" x 96")
- + **Jamb depth: 2.625"**



CUSTOM Options

- + **Low-E Glass**
- + **Low-E Glass + Argon Gas**
- + **Ultra Low-E Glass + Argon Gas**
(May be required for Energy Star rating.)
- + 5/8" or 3/4" flat, 5/8" or 1" contoured, 5/8" contoured valance grids available
- + **Factory mulling of twins, triples and architectural shapes**
- + **Custom sizes available**
- + **Safety latch for sash restriction** (field applied)

+ COLOR OPTIONS**



All products may be ordered to meet Energy Star requirements.

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.

* Screens are not meant to restrain a child from falling through an open window.

** Printing process may affect color shown. Please refer to actual window sample when selecting colors.

