







SERIES 8100


SLIDING WINDOW

- + Insulated glass panels with optimum thermal air space featuring a warm-edge spacer system
- Aluminum-reinforced lock and meeting rails enhance structural integrity
- + Tandem rollers ride easily along friction free glide channel
- + Integrated glide rail for easy sash opening and closing
- + Available in \(^1/4 \frac{1}{2} \frac{1}{4}\)
 or \(^1/3 \frac{1}{3} \frac{1}{3}\) configurations
- + XO or OX 2-lite styles available
- + Double sash locks provide extra security (2 locks standard at 27 ¹/₄" or higher)

- + Beveled exterior frame makes a stylish design statement
- + Factory applied wrap-around foam enhances thermal efficiency around the frame's exterior
- + Fusion-welded frame and sash corners ensure frame durability
- + Sloped sill accommodates easy water run-off
- + Factory-installed half screen standard*
- + Head expander and sill angle are included
- + Jamb depth: 2.75"
- + Transferable limited lifetime warranty



2-lite sliding window



3-lite sliding window

CUSTOM Options

- + Low-E Glass
- + Low-E Glass + Argon Gas
- + Ultra Low-E Glass + Argon Gas (May be required for Energy Star rating)
- + Obscure glass
- + Double strength glass
- + Optional %" or 1" contoured grid and %" or 34" flat grid available
- + Custom sizes cut on 1/8" width and height
- + Factory mulling of twins and triples
- + Charcoal aluminum mesh screen*
- + Lifetime glass breakage warranty











