



## SERIES 151

### SLIDING WINDOW

- + **Beautiful, true brick mould** exterior frame perimeter
- + **Aluminum-reinforced** lock rail and meeting rails add strength
- + **Tandem rollers** ride easily along friction free glide channel
- + **Integrated glide rail** allows easy sash opening and closing
- + **Available in XO or OX** configurations (sliding panel on left or right)
- + **Integrated J-channel** (Series 161 available without J-channel)
- + **Pre-punched nail fin** simplifies installation
- + **Insulated glass panels** featuring warm-edge spacer system
- + **Fusion-welded** frame and sash corners help prevent air and water infiltration
- + **2-lite and 3-lite** configurations available
- + **Half screen** comes standard\*
- + **Jamb depth: 3.277"**
- + **Limited lifetime warranty**



2-lite sliding window

### CUSTOM Options



- + **Low-E Glass**
- + **Low-E Glass + Argon Gas**
- + **Ultra Low-E Glass + Argon Gas**  
(May be required for Energy Star rating)
- + **5/8" or 3/4" flat, 5/8" or 1" contoured, 1 1/8" simulated** divided lite (SDL), 5/8" contoured valance grids available
- + **Paintable or stainable wood jamb extensions** (4 9/16" and 6 9/16")
- + **Factory mulling of twins, triples and factory shapes**
- + **Charcoal aluminum mesh screen\***
- + **Custom sizes available**

+ **COLOR**  
OPTIONS\*\*

White

Almond

Clay



All products may be ordered to meet Energy Star requirements.

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.

\* Screens are not meant to restrain a child from falling through an open window.

\*\* Printing process may affect color shown. Please refer to actual window sample when selecting colors.

